

MANDORLE/ ALMONDS



ITALIA

PVM2535



MONOFASE
Single phase

TRIFASE
Three phase

Pelatrice ventilata per mandorle che ne **rimuove la pellicina esterna**; i semi vanno precedentemente scottati in acqua bollente e poi posti nella macchina che già dal **primo passaggio** ne rimuoverà circa il **78%**, al secondo 94% ed al terzo 99%, delicatamente, senza danneggiare i frutti. Produzione oraria di **25-35 Kg/h**. Motore elettrico disponibile **sia monofase che trifase**.

Ventilated peeler for almonds that **removes the outer skin**; the almonds must be previously blanched in boiling water and then placed in the machine which will remove approximately **78%** of them from the **first step**, 94% for the second and 99% for the third, delicately, without damaging the fruit. Hourly production of **25-35 Kg/h**. Electric motor available both **single-phase and three-phase**.

CARATTERISTICHE/ MAIN SPECS



MOTORE MONOFASE/TRIFASE
SINGLE PHASE/THREE PHASE ENGINE



PRODUZIONE ORARIA 25-35 Kg
HOURLY PRODUCTION 25-35 Kg



DIMENSIONI (cm) 73x40x140
DIMENSION (cm) 73x40x140



PESO 85 Kg
WEIGHT 85 Kg



ITALIA

Sicil Zappa di Giardina Franco & c snc
C.da San Giacomo, Mussomeli (CL) 93014
Tel +39.0934952207
E-mail info@szitalia.it
www.szitalia.it

